

### **CREDITS OF BDO 2002**

#### 1 - PRODUCT

The BDO 2002 and a balanced formulation of wetting agents, oils and additives with high power of dissolution of spilled oil, sludge, etc.

### 2 - USE

The BDO 2002 is especially recommended for cleaning and removal of pollution caused by spillage of oils in water, deck cleaning, docks, tanks, vessels and oil storage lines and in clearing of oil pipelines, treatment of oily water " Slop Tank ". The BDO 2002 is a biodegradable and non-toxic product. Practical tests have shown us that the 2002 BDO has a performance 30% higher than the other products of the same unlike similar BDO 2002 stops the soft, silky purpose; Degradation of BDO 2002 and at least 70% (seventy percent) higher than the more biodegradable products existing in the market and same use. In the cleaning of oil storage tanks operations on platforms BDO 2002 reduces the operating time of at least 50%, opening new jobs for other operations. Because their performance characteristics BDO 2002 can be reused for other washing operations.

## **FEATURES**

- ✓ Net
- ✓ Odour characteristic
- ✓ Nontoxic
- ✓ Biodegradability
- ✓ Flammability not flammable
- $\checkmark$  pH = 7.0 + 0.5
- ✓ Inhibitor Corrosion rate 12 times.
- ✓ Free of aromatic solvents
- ✓ Methanol-free
- ✓ Free of organochlorine



# **DILUTION**

- ✓ Heavy Cleaning dilute the BDO in 2002 to 1: 3 parts by water.
- ✓ Cleaning Average dilute the BDO in 2002 to 1: 5 parts water.
- ✓ Cleaning Branda dilute the BDO in 2002 until 1:30 parts water.

# **ADVANTAGES**

- ✓ Environmentally friendly product.
- ✓ Reduction of operating time around 50% of the wash tank.
- ✓ Reuse of the product \( \) other tanks washing operations and \( \) or other cleaning operations.
- ✓ Wastewater within the limits established by the competent bodies.
- ✓ Vacancies on oil rigs for other operations.
- ✓ Accident risk reduction.
- ✓ Unlike the other products of the same use leaves soft and silky hands.
- ✓ Supporting the treatment of oily water "Slop Tank".
- ✓ Clean and inertiza pipes and pressure vessels without the use of steam.
- ✓ Simplifies operations in E.T.Es and S. A.Os.
- ✓ Rheology modification reducing the oil viscosity of 30 to 50%.
- ✓ Eliminates existing sludge in the tanks of stockpiles, SAOs. and etc.
- ✓ Inhibits corrosion rate in fresh and salt H2O
- ✓ It operates in the oil ducts patency.